

# LightStream™ WXGA 1280x800 Projector with 4,000 Lumens

True-to-Life Color + Smart Design

PJD7526W



Perfect for classrooms or meeting rooms with high ambient light, the ViewSonic® LightStream PJD7526W projector delivers presentations that always shine bright. Thanks to SuperColor™ technology and the brilliance of 4,000 lumens, this projector strikes a perfect balance of color and light to deliver amazing brightness and front-of-screen performance. Whether the shades are drawn, or the room is fully lit, lesson plans, presentations, and multimedia content are brought to life. A smart and intuitive design includes PortAll™ —a hidden MHL/HDMI port perfect for wireless dongles (such as the optional ViewSonic WPG-300) that lets you wirelessly stream multimedia content from a mobile device, or notebook PC, to the projector. Designed with an easy-to-use network management system that lets you remotely control over 250 LightStream projectors, the PJD7526W is great for use in multiple classrooms across an entire campus, or multiple meeting rooms in an office building.

## **Key Features:**

- Best in class color accuracy
- 4,000 lumen high brightness
- Secure MHL/HDMI port
- Network capable
- Smart design

## **Designed for:**

- Education
- Business

# LightStream™ WXGA 1280x800 Projector with 4,000 Lumens



PJD7526W

| Projection Distance |           | Screen Size (4:3 Diagonal) |        |
|---------------------|-----------|----------------------------|--------|
| Inches              | Meters    | Inches                     | Meters |
| 47-51               | 1.2-1.3   | 30                         | 0.8    |
| 62-69               | 1.6-1.7   | 40                         | 1.0    |
| 94-103              | 2.4-2.6   | 60                         | 1.5    |
| 125-137             | 3.3-3.5   | 80                         | 2.0    |
| 156-172             | 4.0-4.4   | 100                        | 2.5    |
| 234-257             | 5.9-6.5   | 150                        | 3.8    |
| 312-343             | 7.9-8.7   | 200                        | 5.1    |
| 390-429             | 9.9-10.9  | 250                        | 6.4    |
| 468-515             | 11.9-13.1 | 300                        | 7.6    |



## Specifications

|                      |                                 |  |
|----------------------|---------------------------------|--|
| <b>DISPLAY</b>       | Type                            | 0.65" Digital Micromirror Device (DLP™)  |
|                      | Resolution                      | 1280 x 800 (native)  |
|                      | Lens                            | 1.2x manual optical zoom / manual optical focus  |
|                      | Keystone                        | Vertical (± 30°) / Horizontal (± 30°)  |
|                      | Size                            | 30 – 300 in. / 0.76 – 7.62 m (diagonal)  |
|                      | Throw Distance                  | 3.0 – 32.8 ft. / 0.9 – 10.0 m  |
|                      | Throw Ratio                     | 1.49–1.79:1  |
|                      | Lamp                            | 250 watt   |
|                      | Light Life                      | 5000/10000(Normal / Eco-mode)  |
|                      | Brightness                      | 4000 lm  |
|                      | Contrast Ratio                  | 22,000:1 (DynamicEco mode)   |
|                      | Aspect Ratio                    | 16:10 (native)   |
| Color Depth          | 30 bits, 1.07B Color (10+10+10) |  |
| <b>INPUT SIGNAL</b>  | Computer and Video              | NTSC M(3.58MHz), 4.43MHz, PAL (B, D, G, H, I, M, N, 60), SECAM (B, D, G, L, L1), SD 480i and 576i, ED 480p and 576p, HD 720p, 1080i, 1080p |
|                      | Frequency                       | Fh: 15–100KHz, Fv: 24–120Hz  |
| <b>COMPATIBILITY</b> | PC                              | Up to 1920x1080  |
|                      | Mac®                            | Up to 1920x1080 (may require MAC adapter)  |
| <b>CONNECTOR</b>     | Digital Input                   | HDMI 1.4 (x1) / HDMI/MHL (x1)  |
|                      | RGB Input                       | 15-pin mini D-Sub (x2)   |
|                      | Composite Input                 | RCA jack (x1)  |
|                      | Audio In                        | 3.5mm mini jack (x2)   |
|                      | Audio Out                       | 3.5mm mini jack (x1)   |
|                      | Video Out                       | 15-pin mini D-Sub (x1)   |
|                      | USB                             | Mini type B (mouse control and maintenance)  |
|                      | LAN                             | RJ45   |
| Control              | RS232                           |  |

|                               |                   |   |
|-------------------------------|-------------------|---|
| <b>AUDIO</b>                  | Speaker           | 16W (x1)  |
| <b>NOISE LEVEL</b>            | Normal / Eco-mode | 32 dB / 28 dB   |
| <b>POWER</b>                  | Voltage           | 100–240VAC (Auto Switching), 50-60Hz (universal)  |
|                               | Consumption       | 315W (max) / <0.5W (stand-by mode)  |
| <b>CONTROLS</b>               | Basic             | Power, keystone/arrow keys, left/blank, menu/exit, right/panel key lock, mode/enter, auto, source   |
|                               | OSD               | Display, Picture, Source, System Setup (Basic), System Setup (Advanced), Information (See user guide for full OSD functionality)                      |
| <b>OPERATING CONDITIONS</b>   | Temperature       | 32–104° F (0–40° C)   |
|                               | Humidity          | 10–90% (non-condensing)   |
|                               | Altitude          | 0–6000 ft (1828.8m)   |
| <b>DIMENSIONS (W x H x D)</b> | Physical          | 14.25 x 9.09 x 4.29 in. / 362 x 231 x 109 mm  |
|                               | Packaging         | 20.47 x 6.5 x 14.96 in. / 520 x 165 x 380 mm  |
| <b>WEIGHT</b>                 | Net               | 6.2 lb. / 2.8 kg  |
|                               | Gross             | 10.1 lb. / 4.6 kg   |
| <b>REGULATIONS</b>            |                   | CB, TUV, GS, UL, CCC, CE, FCC, C-Tick, RoHS, REACH, SVHC, WEEE, ErP, EAC, UkrSEPRO/EMC DOC, UL, COC, TUV-S Mark (Argentina), PSB, KCC, KC, SASO, CECP |
| <b>WARRANTY</b>               |                   | 2-year limited warranty on parts and labor, 1-year limited warranty on lamp, 1st year free Express Exchange® service**                                |

## Optional Accessories (Sold Separately)

|   |             |
|---|-------------|
| Wireless Presentation Gateway Dongle..... | WPG-300     |
| 3D Active Shutter Glasses.....            | PGD-350     |
| Ceiling Mount.....                        | WMK-005     |
| Carrying Case.....                        | PJ-CASE-009 |
| Replacement Lamp.....                     | RLC-096     |
| Extended Warranty.....                    | PJ-EW-07-02 |

## What's in the box?

PJD7526W projector, power cable, VGA cable, Cable Management Hood, remote control with laser (batteries included), Quick Start Guide, ViewSonic Wizard CD (with User Guide)



ViewSonic Corporation's QMS & EMS have been registered to ISO 9001 & ISO 14001, respectively, by TUV NORD.

\*Lamp life may vary based on actual usage and other factors. \*\*One year Express Exchange® service requires product registration. Programs, specifications and availability are subject to change without notice. Selection, offers and programs may vary by country; see your ViewSonic representative for complete details. Corporate names, trademarks stated herein are the property of their respective companies, DLP® and DLP logo are registered trademarks of Texas Instruments. HDMI, the HDMI Logo, and High-Definition Multimedia Interface are trademarks or registered trademarks of HDMI Licensing LLC in the United States and other countries. Copyright © 2015 ViewSonic Corporation. All rights reserved. [18013-00B-06/15]

www.viewsonic.com