

HP Ink Tank 115



Easily print at high volumes for an extremely low cost per page,¹ with a reliable, spill-free ink system.³ Print up to 8,000 pages color or 6,000 pages black,² and produce exceptional quality.



Dynamic security enabled printer. Intended to be used with cartridges using only HP original electronic circuitry. Cartridges with modified or non-HP electronic circuitry may not work, and those that work today may not work in the future.
<http://www.hp.com/go/learnaboutesupplies>

Reliable HP quality

- Count on dark, crisp text, time after time.
- Create borderless brochures, flyers, photos, and other documents that look great - right in your office.
- Count on high-quality prints time after time from the world's #1 printer vendor.⁴

More pages. Less money.

- Print thousands of pages with high-capacity ink tank system.
- Print up to 8,000 pages with a set of HP color bottles or up to 6,000 pages with an HP black ink bottle.²
- Print at high volumes at an extremely low cost-per-page with this high-capacity ink tank system.¹

No mess or waste

- Easily refill your ink tank system with spill-free, resealable bottles.³
- Easily monitor ink levels and replenish Original HP Ink when you want.
- Transparent ink tanks allow you to print with confidence.



¹ HP ink bottles compared to HP ink cartridges. Cost per page based on expected black and composite (cyan/magenta/yellow) page yield results based on HP methodology and continuous printing of ISO/IEC 24712 test pages. Not based on ISO/IEC 24711 test process. Actual yield varies based on content of printed pages and other factors. Some ink from included bottles is used to start up the printer. For more information about fill and yield, see: <http://hp.com/go/learnaboutesupplies>. ² Black and composite color average per bottle (cyan/magenta/yellow) results based on HP methodology from the simulation of continuous printing of ISO/IEC 24712 test pages. Not based on ISO/IEC 24711 test process. The Z included GT51XL black ink bottles are rated to print up to 7,500 test pages each, and are not available for separate sale. Z GT51 or GT51XL black ink bottles are required to print 8000 color test pages. Actual yield varies based on content of printed pages and other factors. Some ink from included bottles is used to start up the printer. For more information about fill and yield, see: <http://www.hp.com/go/learnaboutesupplies>. ³ When used in accordance with set up instructions. ⁴ Based on IDC's Worldwide Quarterly Hardcopy Peripherals Tracker®, 2016 Q4. For shipments all printing devices (inkjet printers, laser printers, copiers and multifunction devices, including production units).

HP Ink Tank 115 Specifications Table

Functions / Multitasking Supported	Print / No
Print Speed⁴	Black (ISO): Up to 8 ppm; Color (ISO): Up to 5 ppm; First Page Out Black: As fast as 14 sec; First Page Out Color: As fast as 18 sec; Black (Draft): Up to 19 ppm; Color (Draft): Up to 16 ppm
Print Resolution	Black (best): Up to 1200 x 1200 rendered dpi; Color (best): Up to 4800 x 1200 optimized dpi color (when printing from a computer and 1200 input dpi)
Print Technology	HP Thermal Inkjet
Printer Drivers Included	HP PCL 3 GUI
Print Cartridges Number	1 black bottle, set of 3 color bottles
Borderless Printing	Yes, up to 210 x 297 mm (A4)
Standard Print languages	HP PCL 3 GUI
Printer Smart Software Features	Manual Duplex
Standard Connectivity	No
Network Capabilities	None
Wireless Capability	No
Mobile Printing Capability	No
Memory	Standard: Integrated; Maximum: Integrated
Processor Speed	360 MHz
Duty Cycle	Monthly, A4: Up to 1,000 pages
Recommended Monthly Page Volume	400 to 800 pages
Media Types Supported	Plain Paper, HP Photo Papers, HP Matte Brochure or Professional Paper, HP Matte Presentation Paper, HP Glossy Brochure or Professional Paper, Photo Inkjet Papers, Matte Inkjet Papers, Glossy Inkjet Papers
Media Weight Supported	A4: 60 to 90 g/m ² ; HP envelopes: 75 to 90 g/m ² ; HP cards: up to 200 g/m ² ; HP 10 x 15 cm photo paper: up to 300 g/m ²
Media Sizes Supported	A4; B5; A6; DL envelope (Note: Many other sizes are also supported. Any size between 3 x 5" and 8.5 x 14")
Media Sizes Custom	76.2 x 127 to 215 x 355 mm
Paper Handling	60-sheet input tray; 25-sheet output tray; Duplex Options: Manual (driver support provided); Auto Document Feeder Capacity: No; Envelope Feeder: No; Standard Paper Trays: 1; Input Capacities: Up to 60 sheets standard; Up to 5 envelopes; No transparencies; Up to 20 cards; Up to 10 sheets labels; Up to 60 sheets legal; Output Capacities: Up to 25 sheets standard; Up to 5 envelopes; No transparencies; Up to 20 cards; Up to 10 sheets labels; Up to 25 sheets legal

What's in the box	ZLB19A HP Ink Tank 115, HP GT51XL Black Ink Bottle (~6000 pages), HP GT52 Cyan Ink Bottle (~8000 pages), HP GT52 Magenta Ink Bottle (~8000 pages), HP GT52 Yellow Ink Bottle (~8000 pages); Ink Caution Flyer; Power Cord; Setup card; Getting started guide (For ink volume and page yield information, visit http://hp.com/go/learnaboutsupplies)
Replacement Cartridges⁵	MOH57AL HP GT51 Black Original Ink Bottle (~4,000 pages); MOH54AL HP GT52 Cyan Original Ink Bottle; MOH55AL HP GT52 Magenta Original Ink Bottle; MOH56AL HP GT52 Yellow Original Ink Bottle (~8,000 pages). Average based on ISO/IEC 24711 or HP testing methodology and continuous printing. Actual yield varies considerably based on content of printed pages and other factors. For more information about fill and yield, see http://hp.com/go/learnaboutsupplies .
Product Dimensions¹	W x D x H: 523 x 284 x 138.5 mm; 20.59 x 11.18 x 5.45 in; Maximum: 523 x 569.75 x 259.7 mm; 20.59 x 22.43 x 10.22 in
Product Weight	3.4 kg; 7.5 lb
Warranty Features	One year of 24/7 world-class technical support services through http://www.hp.com/support ; One-year or 20,000 pages limited hardware warranty, whichever is earlier from the date of purchase; User replaceable parts have separate warranty periods. *Except Argentina - 6 months unlimited pages **Except Colombia - One year limited hardware warranty
Energy Efficiency Compliance	ENERGY STAR [®] qualified
Control Panel	5 LEDs and 5 buttons, also with one ICON LCD for display
Display Description	7 segment + icon LCD
Software Included	HP Printer Software, HP Photo Creations
Compatible Operating Systems	Microsoft [®] Windows [®] 10, 8.1, 8, Windows Vista, Windows [®] XP SP3 or higher (32-bit only); Windows Server 2008 32-bit (SP1 or greater), Windows Server 2008 64-bit (SP1 or greater), Windows Server 2008 R2 64-bit, Windows Server 2008 R2 64-bit (SP1), Windows Server 2012 64-bit, Windows Server 2012 R2 64-bit, Windows Server 2016, OS X v10.10 Yosemite, OS X v10.11 El Capitan, macOS Sierra v10.12 (previously OS X), Linux OS
Minimum System Requirements	PC: Microsoft [®] Windows [®] 10, 8.1, 8, 7: 1 GHz 32-bit (x86) or 64-bit (x64) processor; 2 GB available hard disk space, CD-ROM/DVD drive or Internet connection, USB port, Microsoft [®] Internet Explorer; Windows Vista [®] : 800 MHz 32-bit (x86) processor, 2 GB available hard disk space, CD-ROM/DVD drive or Internet connection, USB port, Microsoft [®] Internet Explorer 8; Windows [®] XP SP3 or higher (32-bit only); any Intel [®] Pentium [®] II, Celeron [®] or 233 MHz compatible processor, 850 MB available hard disk space, CD-ROM/DVD drive or Internet connection, USB port, Microsoft [®] Internet Explorer 8; Windows Server support is provided via the command line installer - Windows Server 2008 32-bit (SP1 or greater); Windows Server 2008 64-bit (SP1 or greater); Windows Server 2008 R2 64-bit, Windows Server 2008 R2 64-bit (SP1); Windows Server 2016; MAC: OS X v10.10 Yosemite, 1.5 GB Available Space, Internet Access; OS X v10.11 El Capitan, 1.5 GB Available Space, Internet Access; macOS Sierra v10.12 (previously OS X), 1.5 GB Available Space, Internet Access
Power²	Power Supply Type: Internal; Power Requirements: Input voltage 100 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3 Hz). High voltage: Input voltage 200 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3 Hz)
Acoustics	Acoustic Power Emissions: 6.0 B(A); Acoustic Pressure Emissions: 47 dB
Operating Environment	Operating Temperature Range: 5 to 40°C; Recommended Operating Temperature: 15 to 30°C; Storage Temperature Range: -40 to 60°C; Non-Operating Humidity Range: 5 to 90% RH (non-condensing); Operating Humidity Range: 15 to 80% RH (non-condensing); Recommended Humidity Operating Range: 20 to 80% RH
Security Management	No

Learn more at hp.com

¹ Dimensions vary as per configuration ² Power requirements are based on the country/region where the printer is sold. Do not convert operating voltages. This will damage the printer and void the product warranty. ³ Speed specifications have been updated to reflect current industry testing methods. ⁴ Either after first page or after first set of ISO test pages. For details see: <http://www.hp.com/go/printerclaims> ⁵ Up to 8000 color or 6000 black pages included: Black and composite color average per bottle (cyan/magenta/yellow) results based on HP methodology and continuous printing of ISO/IEC 24712 test pages. Not based on ISO/IEC 24711 test process. An additional black ink bottle is required to print 8,000 color test pages. Actual yield varies based on content of printed pages and other factors. Some ink from included bottles is used to start up the printer. For more information about fill and yield, see <http://hp.com/go/learnaboutsupplies>. ⁶ HP SureSupply alerts you when you should replace a print cartridge and helps you purchase locally or via the Internet. For more information, visit <http://www.hp.com/learn/suresupply>. Only available with original HP supplies; Internet access required.

